NSN 4820-01-348-7866

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-348-7866

| Pipe Size Accommodated: |
|---|
| 0.500 inches 1st end |
| Thread Class: |
| 3a 2nd end |
| Thread Direction: |
| |
| Right-hand 2nd end |
| Flow Control Device: |
| Stem |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Threaded |
| Maximum Operating Temp: |
| 275.0 degrees fahrenheit single response |
| Connection Style: |
| G72b beveled (pipe) 1st endg45 flareless (tube) 2nd end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Butt weld pipe 1st endthreaded external tube 2nd end |
| Maximum Operating Pressure: |
| 4500.0 pounds per square inch single response |
| Thread Size: |
| 0.438 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Material: |
| Steel comp 316l bodysteel comp 316 stem |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Unf 2nd end |
| Furnished Items And Quantity: |
| 1 ferrule and 1 nut |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Demilitarization: |

A046b0