## NSN 4820-01-349-7222

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-349-7222

View Online at https://aerobasegroup.com/nsn/4820-01-349-7222
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
End Application:
1925-01-247-7110
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
9.000 inches all ends
Face To Face Distance:
11.000 inches
Thickness:
0.688 inches all ends
Bolt Hole Diameter:
0.750 inches all ends
Bolt Circle Diameter:
7.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy bodycopper alloy flow control devicecopper alloy stem
Material Specification:
Astm b61 assn standard single material response body or astm b62 assn standard single material response bodyastm b61 assn standard
single material response flow control device or astm b62 assn standard single material response flow control deviceastm b147, alloy 8a ass
standard single material response stem
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-349-7222

Globe Valve - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A046b0