NSN 4820-01-349-7222

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-349-7222

| View Online at https://aerobasegroup.com/nsn/4820-01-349-7222 |
|--|
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 8 all ends |
| End Application: |
| 1925-01-247-7110 |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 4.000 inches |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 9.000 inches all ends |
| Face To Face Distance: |
| 11.000 inches |
| Thickness: |
| 0.688 inches all ends |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Bolt Circle Diameter: |
| 7.500 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Material: |
| Copper alloy bodycopper alloy flow control devicecopper alloy stem |
| Material Specification: |
| Astm b61 assn standard single material response body or astm b62 assn standard single material response bodyastm b61 assn standard |
| single material response flow control device or astm b62 assn standard single material response flow control deviceastm b147, alloy 8a ass |
| standard single material response stem |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-01-349-7222

Globe Valve - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A046b0