NSN 4820-01-354-3526

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bolt Hole Quantity:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Threaded

8 all ends

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-354-3526

Steel bodysteel flow control devicesteel comp 416 stem

Maximum Operating Temp:
100.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Maximum Operating Pressure:
740.0 pounds per square inch single response
Opening Pressure Setting:
350.0 pounds per square inch
Outside Diameter:
9.000 inches 1st end8.250 inches 2nd end
Thickness:
0.938 inches 1st end1.125 inches 2nd end
First Connection Face To Centerline Distance:
6.375 inches
Bolt Hole Diameter:
0.750 inches 1st end0.875 inches 2nd end
Second Connection Face To Centerline Distance:
6.125 inches
Bolt Circle Diameter:
7.500 inches 1st end6.625 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
6.188 inches 1st end5.000 inches 2nd end
Material:

NSN 4820-01-354-3526

Safety Relief Valve - Page 2 of 2



М	edia	For	Wh	ich	Desi	aned:
IVI	cuia	1 01	***		DESI	uncu.

Air 1st responsesteam 2nd response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0