## NSN 4820-01-355-5770

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-355-5770 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **End Application:** 2350-01-305-0028 **Connection Style:** G46a plain (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends Thready Qty Per Inch (tpi): 20 all ends **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.438 inches all ends **Opening Pressure Setting:** 4.0 pounds per square inch Material: Steel comp 303 body Media For Which Designed: Fuel/oil, hydrocarbon 1st responseoil, lubricating, diester base 2nd responsehydraulic fluid, silicate-ester base 3rd response **Style Designator:** Err-090 **Thread Series Designator:** Unj all ends **Furnished Items And Quantity:** 1 deflector cap Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4820-01-355-5770

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0