NSN 4820-01-359-6356

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-359-6356 **Thread Class:** 2b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 100.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube all ends Thready Qty Per Inch (tpi): 12 all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.625 inches all ends **Opening Pressure Setting:** 150.0 pounds per square inch **Outside Diameter Tube Accommodated:** 1.250 inches all ends Material: Steel comp 303 bodysteel comp 303 flow control deviceplastic polytetrafluoroethylene seat **Material Specification:** Qq-s-763 federal specification single material response bodyqq-s-763 federal specification single material response flow control device Media For Which Designed: Liquid single response **Style Designator:** Err-090

Un all ends Shelf Life:

Thread Series Designator:

N/a

NSN 4820-01-359-6356

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0