NSN 4820-01-362-1030

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-362-1030



Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

30.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.500 inches

Opening Pressure Setting:

38.0 pounds per square inch

Outside Diameter:

7.500 inches 1st end5.000 inches 2nd end

Thickness:

0.625 inches 1st end0.438 inches 2nd end

First Connection Face To Centerline Distance:

4.875 inches

Bolt Hole Diameter:

0.750 inches 1st end0.625 inches 2nd end

Second Connection Face To Centerline Distance:

5.125 inches

Bolt Circle Diameter:

6.000 inches 1st end3.875 inches 2nd end

Flange Face Design:

Plain all ends

Material:

Steel bodysteel comp 316 flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

Shelf Life:

N/a

NSN 4820-01-362-1030

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

