NSN 4820-01-362-1030

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-362-1030

Dolled
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
30.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Opening Pressure Setting:
38.0 pounds per square inch
Outside Diameter:
7.500 inches 1st end5.000 inches 2nd end
Thickness:
0.625 inches 1st end0.438 inches 2nd end
First Connection Face To Centerline Distance:
4.875 inches
Bolt Hole Diameter:
0.750 inches 1st end0.625 inches 2nd end
Second Connection Face To Centerline Distance:
5.125 inches
Bolt Circle Diameter:
6.000 inches 1st end3.875 inches 2nd end
Flange Face Design:
Plain all ends
Material:
Steel bodysteel comp 316 flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Shelf Life:
N/a

NSN 4820-01-362-1030

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0