NSN 4820-01-363-1911

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-363-1911
Flow Control Device:
Poppet
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
End Application:
Acft, type c-17a, serd 490007
Length:
1.133 inches all ends
Thready Qty Per Inch (tpi):
18 all ends
Adjustable Pressure Range:
+0.5/+15.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Outside Diameter:
0.630 inches all ends
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Stainless steel body
Media For Which Designed:
Hydrogen 1st response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type i, class 1 military specification single treatment response
Style Designator:
C6 straight thru
Thread Series Designator:
Npt all ends
Furnished Items And Quantity:
1 deflector cap and 1 washer and 1 spring
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

NSN 4820-01-363-1911

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.