NSN 4820-01-363-2100

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-363-2100

Flow Control Device:

Disk

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

425.0 degrees fahrenheit 1st response150.0 degrees fahrenheit 2nd response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.500 inches

Maximum Operating Pressure:

150.0 pounds per square inch 1st response250.0 pounds per square inch 2nd response

Outside Diameter:

5.062 inches all ends

Thickness:

0.812 inches all ends

First Connection Face To Centerline Distance:

4.750 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

4.750 inches

Bolt Circle Diameter:

3.938 inches all ends

Flange Face Design:

Plain all ends

Material:

Copper alloy bodynickel alloy flow control devicenickel alloy seatnickel alloy stem

Media For Which Designed:

Steam 1st responsewater-oil-gas 2nd response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4820-01-363-2100

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

