## NSN 4820-01-363-2100

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-363-2100 Flow Control Device: Disk **Bolt Hole Quantity:** 6 all ends **Maximum Operating Temp:** 425.0 degrees fahrenheit 1st response150.0 degrees fahrenheit 2nd response **Valve Operation Method:** Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 1.500 inches **Maximum Operating Pressure:** 150.0 pounds per square inch 1st response250.0 pounds per square inch 2nd response **Outside Diameter:** 5.062 inches all ends Thickness: 0.812 inches all ends **First Connection Face To Centerline Distance:** 4.750 inches **Bolt Hole Diameter:** 0.562 inches all ends **Second Connection Face To Centerline Distance:** 4.750 inches **Bolt Circle Diameter:** 3.938 inches all ends Flange Face Design: Plain all ends Material: Copper alloy bodynickel alloy flow control devicenickel alloy seatnickel alloy stem Media For Which Designed: Steam 1st responsewater-oil-gas 2nd response **Style Designator:** Err-090 Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 4820-01-363-2100

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0