

View Online at <https://aerobasegroup.com/nsn/4820-01-365-2853>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 1st end 6 2nd end

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Adjustable Pressure Range:

+72.0/+88.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Outside Diameter:

6.625 inches 1st end 5.562 inches 2nd end

Thickness:

0.500 inches 1st end 0.438 inches 2nd end

First Connection Face To Centerline Distance:

5.375 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

5.375 inches

Bolt Circle Diameter:

5.500 inches 1st end 4.438 inches 2nd end

Flange Face Design:

Plain all ends

Material:

Copper alloy 922 body nickel alloy flow control device nickel alloy seat steel comp 303 stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0