## NSN 4820-01-365-5232

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-365-5232

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Blue ridge class lcc-19
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+15.0/+19.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.312 inches all ends
First Connection Face To Centerline Distance:
3.094 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.094 inches
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Style Designator:

Err-090

## NSN 4820-01-365-5232

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0