NSN 4820-01-369-1992

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-369-1992

| Disk | |
|--|--|
| Bonnet Type: | |
| Inside spring | |
| Bonnet Attachment Method: | |
| Bolted | |
| Disk Loading Method: | |
| Spring | |
| Bolt Hole Quantity: | |
| 6 all ends | |
| Maximum Operating Temp: | |
| 150.0 degrees fahrenheit single response | |
| End Application: | |
| Nimitz class cvn | |
| Valve Operation Method: | |
| Automatic | |
| Flange Shape: | |
| Round with holes all ends | |
| Connection Type: | |
| Flange all ends | |
| Valve Size: | |
| 2.500 inches | |
| Adjustable Pressure Range: | |
| +10.0/+16.0 pounds per square inch | |
| Maximum Operating Pressure: | |
| 150.0 pounds per square inch single response | |
| Outside Diameter: | |
| 6.125 inches all ends | |
| Thickness: | |
| 0.562 inches all ends | |
| First Connection Face To Centerline Distance: | |
| 5.500 inches | |
| Bolt Hole Diameter: | |
| 0.562 inches all ends | |
| Second Connection Face To Centerline Distance: | |
| 5.500 inches | |
| Bolt Circle Diameter: | |
| 5.000 inches all ends | |
| Flange Face Design: | |
| Plain all ends | |
| Material: | |
| Copper alloy body | |
| | |

NSN 4820-01-369-1992

Safety Relief Valve - Page 2 of 2



| Media For Which Designe | Which Designe | ed |
|-------------------------|---------------|----|
|-------------------------|---------------|----|

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0