## NSN 4820-01-369-5165

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-369-5165

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Adjustable Pressure Range:
+45.0/+75.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
6.125 inches all ends
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
5.500 inches
Bolt Circle Diameter:
5.000 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy bodycopper alloy flow control devicecopper alloy seat
Material Specification:

Astmb61 assn standard single material response bodyastmb164 assn standard single material response flow control deviceastmb164 assn standard single material response seat

## NSN 4820-01-369-5165

Safety Relief Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0