NSN 4820-01-370-1208

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-370-1208

Threaded
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Adjustable Pressure Range:
+3.0/+8.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
7.687 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
6.500 inches
Bolt Hole Diameter:
0.688 inches all ends
Second Connection Face To Centerline Distance:
6.500 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Special Features:
No gagging device
Material:
Bronze bodynickel alloy flow control devicenickel alloy seat

NSN 4820-01-370-1208

Safety Relief Valve - Page 2 of 2



Media	For	Which	Design	ed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0