## NSN 4820-01-370-1208

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-370-1208

Threaded					
Disk Loading Method:					
Spring					
Bolt Hole Quantity:					
4 all ends					
Maximum Operating Temp:					
150.0 degrees fahrenheit single response					
Valve Operation Method:					
Automatic					
Flange Shape:					
Round with holes all ends					
Connection Type:					
Flange all ends					
Valve Size:					
4.000 inches					
Adjustable Pressure Range:					
+3.0/+8.0 pounds per square inch					
Maximum Operating Pressure:					
250.0 pounds per square inch single response					
Outside Diameter:					
7.687 inches all ends					
Thickness:					
0.938 inches all ends					
First Connection Face To Centerline Distance:					
6.500 inches					
Bolt Hole Diameter:					
0.688 inches all ends					
Second Connection Face To Centerline Distance:					
6.500 inches					
Bolt Circle Diameter:					
5.500 inches all ends					
Flange Face Design:					
Plain all ends					
Special Features:					
No gagging device					
Material:					
Bronze bodynickel alloy flow control devicenickel alloy seat					

## NSN 4820-01-370-1208

Safety Relief Valve - Page 2 of 2



Me	dia	For	Which	Design	ed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0