

View Online at <https://aerobasegroup.com/nsn/4820-01-370-1208>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

4.000 inches

Adjustable Pressure Range:

+3.0/+8.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Outside Diameter:

7.687 inches all ends

Thickness:

0.938 inches all ends

First Connection Face To Centerline Distance:

6.500 inches

Bolt Hole Diameter:

0.688 inches all ends

Second Connection Face To Centerline Distance:

6.500 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Special Features:

No gagging device

Material:

Bronze bodynickel alloy flow control devicenickel alloy seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0