

View Online at <https://aerobasegroup.com/nsn/4820-01-373-3073>

Thread Direction:

Right-hand all ends

Flow Control Device:

Needle

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Maximum Operating Temp:

350.0 degrees fahrenheit single response

End Application:

5865-01-338-0526

Connection Style:

G9 plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external pipe all ends

Maximum Operating Pressure:

5000.0 pounds per square inch single response

Thread Size:

0.250 inches all ends

Material:

Steel comp 316 bodysteel comp 316 flow control deviceplastic polychlorotrifluoroethylene seatsteel comp 316 stem

Material Specification:

Astma182 assn standard single material response bodyastma182 assn standard single material response flow control deviceastma182 assn standard single material response seatastma182 assn standard single material response stem

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Furnished Items And Quantity:

1 handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0