NSN 4820-01-373-6991

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside screw

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-373-6991

Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+72.0/+88.0 pounds per square inch
Maximum Operating Pressure:
225.0 pounds per square inch single response
Outside Diameter:
5.000 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
4.875 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy 922 bodynickel alloy flow control devicenickel alloy seatsteel comp 303 stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

NSN 4820-01-373-6991

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0