Fluid Pressure Regulating Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-374-3005

Body Material. Brass Body Style: Straight thu Media For Which Designed: Air or water First End Connection Type: Threaded internal pipe First End Connection Type: Threaded internal pipe First End Thread Size And Series/type Designator: 1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Intel Pressure Rating: 140.0 pounds per square inch Filter: Not included Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig: Az1100	Body Material:
Body Style: Braight thru Media For Which Designed: Air or water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outle Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximun Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
Straight thruMedia For Which Designed:Air or waterFirst End Connection Type:Threaded internal pipeFirst End Style Designator:PlainFirst End Thread Size And Series/type Designator:1/4-18 nptFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalFlow Control Device:DiskEnd Connection Quantity:2Outlet Pressure Range:+2.0/+30.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximun Inlet Pressure Rating:14.0.0 pounds per square inchFilter:Not includedShelf Life:NatiNational Consertion:National Consertion:National Consertion:National Consertion:Maximum Intel Pressure Rating:14.0.0 pounds per square inchFilter:Not includedShelf Life:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion:Maximum Intel Pressure Rating:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion:National Consertion: <th></th>	
Mair or Water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: Na Idit Of Measure: - Demilitarization: No Fig:	
Air or water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outle Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Autoratic single stage Valve Loading Method: Spring Maximun Intel Pressure Rating: 140.0 pounds per square inch Filter: Not included Sheff Life: Na Unit Of Measure: - Disk Fig: Na	-
First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Intet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: - Demilitarization: No	-
Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximun Inlet Pressure Rating: Not included Shelf Life: Nva Idof Measure: Pilot Shelf Life: Na Int of Measure: Pimilitarization: No Filig:	
First End Style Designator:PlainFirst End Thread Size And Series/type Designator:1/4-18 nptFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalFlow Control Device:DiskEnd Connection Quantity:2Outlet Pressure Range:+2.0/+30.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:140.0 pounds per square inchFilte:Not includedShelf Life:NotNotFilte:NotSpringShelf Life:NotNoFilte:NoFilte:NoFilte:NoFilte:Filte:NoFilte:Filte:NoFilte:NoFilte:NoFilte:NoFilte:NoFilte:NoFilte:NoFilte:NoFilte:NoFilte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte:Filte: <td< th=""><th></th></td<>	
PlainFirst End Thread Size And Series/type Designator:1/4-18 nptFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalFow Control Device:DiskEnd Connection Quantity:2Outlet Pressure Range:+2.0/+30.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:140.0 pounds per square inchFilter:Not includedSheff Life:N/aUnit of Measure:Filter:NoPinilitarization:NoFig:	
First End Thread Size And Series/type Designator: 1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: Na Unit of Measure: - Tomilitarization: No	
1/4-18 npt First End Thread Direction: Right-hand Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
First End Thread Direction:Right-handSecond End Relationship With First End:IdenticalIdenticalFlow Control Device:DiskEnd Connection Quantity:2Outlet Pressure Range:+2.0/+30.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:140.0 pounds per square inchFilter:Not includedShelf Life:N/aInit Of Measure:Pemilitarization:NoFilg:	
Right-hand Second End Relationship With First End: Identical How Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Penilitarization: No Filg:	
Second End Relationship With First End: Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: 42.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maxinum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Identical Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: 42.0/+30.0 pounds per square inch 42.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	-
Flow Control Device: Disk End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
Disk End Connection Quantity: Characteristic Connection Quantity:	
End Connection Quantity: 2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
2 Outlet Pressure Range: +2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Dint Of Measure: - Demilitarization: No Fig:	
Outlet Pressure Range:+2.0/+30.0 pounds per square inchRegulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:140.0 pounds per square inchFilter:Not includedShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	
+2.0/+30.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Regulation Type:Automatic single stageValve Loading Method:SpringMaximum Inlet Pressure Rating:140.0 pounds per square inchFilter:Not includedShelf Life:N/aUnit Of Measure:Pemilitarization:NoFilg:	
Automatic single stage Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Valve Loading Method: Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Spring Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Maximum Inlet Pressure Rating: 140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: - No Filter: No Fiig:	
140.0 pounds per square inch Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Filter: Not included Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Not included
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A21100	Fiig:
	A21100