NSN 4820-01-376-9852

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-376-9852

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
434.0 cubic feet per minute
Maximum Operating Temp:
165.0 degrees fahrenheit single response
End Application:
Seawolf class ssn
Connection Style:
Socket err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+4001.0/+5499.0 pounds per square inch
Maximum Operating Pressure:
6000.0 pounds per square inch single response
Criticality Code Justification:
Zzzy
Opening Pressure Setting:
4900.0 pounds per square inch
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 federal specification single material response stem
Media For Which Designed:
Nitrogen, gaseous single response
Style Designator:
Err-090
Reference Number Differentiating Characteristics:
Cleaned in accordance with mil-i-52211
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-01-376-9852

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0