NSN 4820-01-379-2083

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-379-2083

bonnet Type.
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Opening Pressure Setting:
45.0 pounds per square inch
Outside Diameter:
2.000 inches 2nd end
Thickness:
0.625 inches 1st end
First Connection Face To Centerline Distance:
4.750 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
3.625 inches 1st end
Material:
Steel stem
Style Designator:
Err-090

NSN 4820-01-379-2083

Safety Relief Valve - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0