NSN 4820-01-379-2083

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-379-2083

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.500 inches

Opening Pressure Setting:

45.0 pounds per square inch

Outside Diameter:

2.000 inches 2nd end

Thickness:

0.625 inches 1st end

First Connection Face To Centerline Distance:

4.750 inches

Bolt Hole Diameter:

0.750 inches 1st end

Second Connection Face To Centerline Distance:

4.875 inches

Bolt Circle Diameter:

4.750 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

3.625 inches 1st end

Material:

Steel stem

Style Designator:

Err-090

NSN 4820-01-379-2083

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

