## NSN 4820-01-382-2073

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-382-2073

| Pipe Size Accommodated:                    |  |  |  |  |  |
|--|--|--|--|--|--|
| 0.500 inches 2nd end                       |  |  |  |  |  |
| Flow Control Device:                       |  |  |  |  |  |
| Disk                                       |  |  |  |  |  |
| Bonnet Type:                               |  |  |  |  |  |
| Inside spring                              |  |  |  |  |  |
| Bonnet Attachment Method:                  |  |  |  |  |  |
| Integral                                   |  |  |  |  |  |
| Disk Loading Method:                       |  |  |  |  |  |
| Spring                                     |  |  |  |  |  |
| Bolt Hole Quantity:                        |  |  |  |  |  |
| 3 1st end                                  |  |  |  |  |  |
| Connection Style:                          |  |  |  |  |  |
| Socket with brazing ring err-100           |  |  |  |  |  |
| Valve Operation Method:                    |  |  |  |  |  |
| Manual                                     |  |  |  |  |  |
| Flange Shape:                              |  |  |  |  |  |
| Round with holes 1st end                   |  |  |  |  |  |
| Connection Type:                           |  |  |  |  |  |
| Unthreaded internal pipe 2nd end           |  |  |  |  |  |
| Adjustable Pressure Range:                 |  |  |  |  |  |
| +15.0/+19.0 pounds per square inch         |  |  |  |  |  |
| Outside Diameter:                          |  |  |  |  |  |
| 3.562 inches 2nd end                       |  |  |  |  |  |
| Thickness:                                 |  |  |  |  |  |
| 0.375 inches 1st end                       |  |  |  |  |  |
| Bolt Hole Diameter:                        |  |  |  |  |  |
| 0.375 inches 1st end                       |  |  |  |  |  |
| Bolt Circle Diameter:                      |  |  |  |  |  |
| 2.438 inches 1st end                       |  |  |  |  |  |
| Flange Face Design:                        |  |  |  |  |  |
| Plain 1st end                              |  |  |  |  |  |
| Material:                                  |  |  |  |  |  |
| Nickel alloy flow control device           |  |  |  |  |  |
| Style Designator:                          |  |  |  |  |  |
| Err-090                                    |  |  |  |  |  |
| Specification Data:                        |  |  |  |  |  |
| 81349-mil-v-20065 government specification |  |  |  |  |  |
| Specification Or Standard:                 |  |  |  |  |  |
| A2 type and c class                        |  |  |  |  |  |
| Shelf Life:                                |  |  |  |  |  |
| N/a  |  |  |  |  |  |

## NSN 4820-01-382-2073

Safety Relief Valve - Page 2 of 2



|  | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-20065 spec.