NSN 4820-01-382-2073

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-382-2073

Pipe Size Accommodated:					
0.500 inches 2nd end					
Flow Control Device:					
Disk					
Bonnet Type:					
Inside spring					
Bonnet Attachment Method:					
Integral					
Disk Loading Method:					
Spring					
Bolt Hole Quantity:					
3 1st end					
Connection Style:					
Socket with brazing ring err-100					
Valve Operation Method:					
Manual					
Flange Shape:					
Round with holes 1st end					
Connection Type:					
Unthreaded internal pipe 2nd end					
Adjustable Pressure Range:					
+15.0/+19.0 pounds per square inch					
Outside Diameter:					
3.562 inches 2nd end					
Thickness:					
0.375 inches 1st end					
Bolt Hole Diameter:					
0.375 inches 1st end					
Bolt Circle Diameter:					
2.438 inches 1st end					
Flange Face Design:					
Plain 1st end					
Material:					
Nickel alloy flow control device					
Style Designator:					
Err-090					
Specification Data:					
81349-mil-v-20065 government specification					
Specification Or Standard:					
A2 type and c class					
Shelf Life:					
N/a					

NSN 4820-01-382-2073

Safety Relief Valve - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-20065 spec.