NSN 4820-01-383-5651

Stop-check Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-383-5651

Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
775.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Valve Size:
5.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
10.000 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
7.125 inches
Bolt Hole Diameter:
0.875 inches all ends
Second Connection Face To Centerline Distance:
7.125 inches
Bolt Circle Diameter:
8.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
7.312 inches all ends
Material:
Steel seat

NSN 4820-01-383-5651

Stop-check Valve - Page 2 of 2



Steam single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0