## NSN 4820-01-391-3306

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-391-3306

21.
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
14 1st end
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
6.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
98.0 pounds per square inch
Outside Diameter:
12.375 inches 1st end
Thickness:
0.625 inches 1st end
First Connection Face To Centerline Distance:
9.500 inches
Bolt Hole Diameter:
0.688 inches all ends
Second Connection Face To Centerline Distance:
8.750 inches
Bolt Circle Diameter:
8.875 inches 2nd end
Flange Face Design:
Plain all ends
Material:
Steel comp 303 stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

## NSN 4820-01-391-3306

Safety Relief Valve - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0