NSN 4820-01-391-9797

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-391-9797

Flow Control Device:
Disk
Valve Discharge Flow Rate:
44700.0 pounds per hour
Bolt Hole Quantity:
8 2nd end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+696.0/+760.0 pounds per square inch
Maximum Operating Pressure:
725.0 pounds per square inch single response
Opening Pressure Setting:
625.0 pounds per square inch
Outside Diameter:
9.000 inches 1st end
Thickness:
1.125 inches 1st end
Bolt Hole Diameter:
0.875 inches 2nd end
Bolt Circle Diameter:
7.250 inches 1st end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
5.500 inches 1st end
Special Features:
Mod2 2-1/2j x 3-1/2hnj
Material:
Steel stem
Material Specification:
Astm a53 assn standard single material response stem
Style Designator:
Err-090
Furnished Items And Quantity:

1 lever

NSN 4820-01-391-9797

Safety Relief Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0