

View Online at <https://aerobasegroup.com/nsn/4820-01-391-9797>

Flow Control Device:

Disk

Valve Discharge Flow Rate:

44700.0 pounds per hour

Bolt Hole Quantity:

8 2nd end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Adjustable Pressure Range:

+696.0/+760.0 pounds per square inch

Maximum Operating Pressure:

725.0 pounds per square inch single response

Opening Pressure Setting:

625.0 pounds per square inch

Outside Diameter:

9.000 inches 1st end

Thickness:

1.125 inches 1st end

Bolt Hole Diameter:

0.875 inches 2nd end

Bolt Circle Diameter:

7.250 inches 1st end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

5.500 inches 1st end

Special Features:

Mod2 2-1/2j x 3-1/2hnj

Material:

Steel stem

Material Specification:

Astm a53 assn standard single material response stem

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0