NSN 4820-01-406-8792

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk Loading Method:

Water-oil-gas single response

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-406-8792

Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
450.0 degrees fahrenheit 1st response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+262.0/+304.0 pounds per square inch
Maximum Operating Pressure:
225.0 pounds per square inch 2nd response
Outside Diameter:
4.250 inches 1st end
Thickness:
0.438 inches 1st end
First Connection Face To Centerline Distance:
1.510 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
1.510 inches
Bolt Circle Diameter:
3.125 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches 2nd end
Raised Face Diameter:
2.000 inches 1st end
Material:
Stainless steel stem
Media For Which Designed:

NSN 4820-01-406-8792

Safety Relief Valve - Page 2 of 2



Style	Designator:
Err-09	0

Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0