NSN 4820-01-406-8794

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-406-8794

Thread Class:

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

300.0 degrees fahrenheit single response

End Application:

6685-01-356-6542

Connection Style:

G43 external seat for gasket seal (boss) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external boss all ends

Maximum Operating Pressure:

3.0 pounds per square inch single response

Thread Size:

0.563 inches all ends

Seat Angle:

37.0 degrees all ends

Opening Pressure Setting:

3.0 pounds per square inch

Special Features:

Anodize mil-a-8625, type ii black

Material:

Aluminum alloy 2011 seat

Media For Which Designed:

Air single response

Style Designator:

Err-090

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

NSN 4820-01-406-8794

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

