NSN 4820-01-407-0682

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-407-0682

Flow Control Device:

Disk

Bonnet Type:
Inside spring

Bonnet Attachment Method: Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

400.0 degrees fahrenheit single response

End Application:

Seawolf class ssn

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.500 inches

Maximum Operating Pressure:

285.0 pounds per square inch single response

Opening Pressure Setting:

15.0 pounds per square inch

Outside Diameter:

5.000 inches all ends

Thickness:

0.688 inches all ends

First Connection Face To Centerline Distance:

4.750 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

4.750 inches

Bolt Circle Diameter:

3.875 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

NSN 4820-01-407-0682

Safety Relief Valve - Page 2 of 2



Raised Face Diameter:
2.875 inches all ends
Material:
Stainless steel stem
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0