

View Online at <https://aerobasegroup.com/nsn/4820-01-408-1628>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

1000.0 degrees fahrenheit single response

Minimum Operating Temp:

100.0 degrees fahrenheit

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Maximum Operating Pressure:

275.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Thickness:

0.750 inches all ends

First Connection Face To Centerline Distance:

4.000 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

4.000 inches

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

3.062 inches all ends

Material:

Steel uns j03002 body

Media For Which Designed:

Oil single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0