NSN 4820-01-411-6259

Body Material:

Body Style:

Steel, corrosion resisting

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-411-6259

Body Style:
Straight thru
Stem Material:
Steel, corrosion resisting
Media For Which Designed:
Nitrogen, gaseous
First End Connection Type:
Unthreaded internal pipe
First End Style Designator:
Socket
First End Pipe Size Accommodated:
0.500 inches
Second End Relationship With First End:
Not identical
Second End Connection Type:
Unthreaded internal pipe
Second End Style Designator:
Socket
Second End Pipe Size Accommodated:
0.375 inches
Onet Metarials
Seat Material:
Plastic
Plastic
Plastic Flow Control Device:
Plastic Flow Control Device: Diaphragm
Plastic Flow Control Device: Diaphragm End Connection Quantity:
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range:
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type:
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method:
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Dome
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Dome Remote Actuation Method:
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Dome Remote Actuation Method: Diaphragm
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Dome Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating:
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Dome Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 6000.0 pounds per square inch
Plastic Flow Control Device: Diaphragm End Connection Quantity: 2 Outlet Pressure Range: +1.0/+2000.0 pounds per square inch Regulation Type: Automatic single stage Valve Loading Method: Dome Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 6000.0 pounds per square inch Filter:

165.0 degrees fahrenheit

NSN 4820-01-411-6259

Fluid Pressure Regulating Valve - Page 2 of 2



he			

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100