## NSN 4820-01-412-2686

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-412-2686

Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Mdl-1771-t
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+19.0/+22.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.812 inches all ends
Thickness:
0.437 inches all ends
First Connection Face To Centerline Distance:
2.312 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
2.313 inches
Bolt Circle Diameter:
2.687 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Non magnetic service
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response

## NSN 4820-01-412-2686

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0