NSN 4820-01-419-2624

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-419-2624

Thread Direction:
Right-hand all ends
Flow Control Device:
Ball
Disk Loading Method:
Spring
Maximum Operating Temp:
350.0 degrees fahrenheit single response
End Application:
Belknap class cg
Connection Style:
Plain, optional end (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Mounting Position:
Horizontal
Maximum Operating Pressure:
1000.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
0.375 inches all ends Opening Pressure Setting:
Opening Pressure Setting:
Opening Pressure Setting: 10.0 pounds per square inch
Opening Pressure Setting: 10.0 pounds per square inch Material:
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed:
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator:
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru Thread Series Designator:
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru Thread Series Designator: Npt all ends
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life:
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure:
Opening Pressure Setting: 10.0 pounds per square inch Material: Steel comp 440c flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Straight thru Thread Series Designator: Npt all ends Shelf Life: N/a Unit Of Measure: Demilitarization: