

View Online at <https://aerobasegroup.com/nsn/4820-01-419-6491>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

400.0 degrees fahrenheit 2nd response

End Application:

Wasp class lhd

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Maximum Operating Pressure:

275.0 pounds per square inch 1st response

Opening Pressure Setting:

182.0 pounds per square inch

Outside Diameter:

6.000 inches 2nd end

Thickness:

0.938 inches 1st end

First Connection Face To Centerline Distance:

5.500 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

5.688 inches

Bolt Circle Diameter:

6.000 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

5.000 inches 1st end

Material:

Stainless steel body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Furnished Items And Quantity:

1 lever

Specification Data:

81349-mil-v-24332 government specification

Specification Or Standard:

150 class and a grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.