## NSN 4820-01-420-5231

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-420-5231

Thread Direction:
Right-hand all ends
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-100.0 degrees fahrenheit
End Application:
Aircraft, hercules c
Connection Style:
G4 gasket sea (boss) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal tube 2nd end
Maximum Operating Pressure:
1000.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
25.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 2nd end
Special Features:
With polytetrafluoroethylene seal
Material:
Stainless steel seat
Media For Which Designed:
Water-oil-gas single response
Style Designator:
C8 straight through note: to be used for valve bodies of one section only.
Thread Series Designator:
Nptf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-01-420-5231

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0