

View Online at <https://aerobasegroup.com/nsn/4820-01-420-5919>

Flow Control Device:

Diaphragm

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

10 all ends

Maximum Operating Temp:

180.0 degrees fahrenheit single response

Minimum Operating Temp:

-40.0 degrees celsius

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

5.000 inches

Maximum Operating Pressure:

225.0 pounds per square inch single response

Outside Diameter:

9.060 inches all ends

Face To Face Distance:

15.750 inches

Thickness:

0.590 inches all ends

Bolt Hole Diameter:

0.688 inches all ends

Bolt Circle Diameter:

7.813 inches all ends

Flange Face Design:

Plain all ends

Material:

Rubber synthetic flow control device

Material Specification:

Qq-n-288, comp b federal specification single material response seat

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-std-417 spec.