NSN 4820-01-420-8058

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-420-8058

| Flow Control Device: |
|--|
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 6 all ends |
| Maximum Operating Temp: |
| 475.0 degrees fahrenheit single response |
| End Application: |
| Supply class aoe |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal |
| Valve Size: |
| 2.500 inches |
| Maximum Operating Pressure: |
| 100.0 pounds per square inch single response |
| Outside Diameter: |
| 6.125 inches all ends |
| Face To Face Distance: |
| 9.000 inches |
| Thickness: |
| 0.500 inches all ends |
| Bolt Hole Diameter: |
| 0.563 inches all ends |
| Bolt Circle Diameter: |
| 5.000 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Material: |
| Nickel alloy flow control device |
| Style Designator: |
| Straight through flanged ends |
| Shelf Life: |

N/a

NSN 4820-01-420-8058

Stop-check Valve - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A530b0