## NSN 4820-01-421-8821

Safety Relief Valve - Page 1 of 2

**Bonnet Type:** 



View Online at https://aerobasegroup.com/nsn/4820-01-421-8821

Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
300.0 degrees fahrenheit single response
End Application:
Mars class afs
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+11.0/+17.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.375 inches all ends
First Connection Face To Centerline Distance:
2.125 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
2.125 inches
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
4.075 in alcan all and a

1.375 inches all ends

## NSN 4820-01-421-8821

Safety Relief Valve - Page 2 of 2



Materiai:
Stainless steel seat
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 cap
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0