NSN 4820-01-422-4112

Check Valve - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/4820-01-422-4112

| 2b 1st end |
|--|
| Thread Direction: |
| Right-hand all ends |
| End Application: |
| 3930-01-384-5310; |
| Connection Style: |
| Swivel nut, gasket seal (tube) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal tube 1st end |
| Mounting Position: |
| Horizontal or vertical |
| Thready Qty Per Inch (tpi): |
| 14 all ends |
| Maximum Operating Pressure: |
| 20670.0 kilopascals single response |
| Thread Size: |
| 1.000 inches all ends |
| Opening Pressure Setting: |
| 450.0 kilopascals |
| Outside Diameter Tube Accommodated: |
| 0.625 inches all ends |
| Material: |
| Steel |
| Surface Treatment: |
| Zinc and chromate |
| Surface Treatment Specification: |
| P mfr ref single treatment response |
| Style Designator: |
| Cross |
| Supplementary Features: |
| Flow control device: plug |
| Thread Series Designator: |
| Uns all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 4820-01-422-4112

Check Valve - Page 2 of 2



Fiig:

A530b0