NSN 4820-01-422-7246

Stop-check Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Renewable Seat Ring Type:

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-422-7246

Pressed-in
Bolt Hole Quantity:
12 all ends
End Application:
Strategic sealift conversion ships class
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Mounting Position:
Horizontal
Valve Size:
10.000 inches
Outside Diameter:
16.000 inches all ends
Face To Face Distance:
20.000 inches
Thickness:
1.187 inches all ends
Bolt Hole Diameter:
1.000 inches all ends
Bolt Circle Diameter:
14.250 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Manual handwheel control
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-288 federal specification single material response seat

NSN 4820-01-422-7246

Stop-check Valve - Page 2 of 2



N	Λ	edia	For	Which	Design	ned:

Water, fresh single response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0