NSN 4820-01-423-2016

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-423-2016

Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
12 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
End Application:
Navy weapon system code le fire fighting equipment
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
6.000 inches
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
10.125 inches all ends
Face To Face Distance:
20.000 inches
Thickness:
1.190 inches all ends
Bolt Hole Diameter:
0.694 inches all ends
Bolt Circle Diameter:
8.880 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy body
Media For Which Designed:
Water, salt single response
Style Designator:
Straight through flanged ends
Shelf Life:

N/a

NSN 4820-01-423-2016

Lift-check Valve - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A530b0