NSN 4820-01-423-2025

Lift-check Valve - Page 1 of 2



Elit Gleck valve Tage For 2
View Online at https://aerobasegroup.com/nsn/4820-01-423-2025
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
250.0 degrees fahrenheit
End Application:
Navy weapon sysyem code le fire fighting equipment
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal
Valve Size:
2.000 inches
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
11.500 inches all ends
Face To Face Distance:
11.500 inches
Thickness:
0.810 inches all ends
Bolt Hole Diameter:
0.694 inches all ends
Bolt Circle Diameter:
4.440 inches all ends
Flange Face Design:
Plain all ends
Material:

Nickel alloy body

Media For Which Designed:

Water, salt single response

Style Designator:

Straight through flanged ends

NSN 4820-01-423-2025

Lift-check Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0