NSN 4820-01-423-2025

Lift-check Valve - Page 1 of 2



| Elit Gleck valve Tage For 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/4820-01-423-2025 |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 6 all ends |
| Maximum Operating Temp: |
| 250.0 degrees fahrenheit single response |
| Minimum Operating Temp: |
| 250.0 degrees fahrenheit |
| End Application: |
| Navy weapon sysyem code le fire fighting equipment |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Mounting Position: |
| Horizontal |
| Valve Size: |
| 2.000 inches |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch single response |
| Outside Diameter: |
| 11.500 inches all ends |
| Face To Face Distance: |
| 11.500 inches |
| Thickness: |
| 0.810 inches all ends |
| Bolt Hole Diameter: |
| 0.694 inches all ends |
| Bolt Circle Diameter: |
| 4.440 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Material: |

Nickel alloy body

Media For Which Designed:

Water, salt single response

Style Designator:

Straight through flanged ends

NSN 4820-01-423-2025

Lift-check Valve - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0