NSN 4820-01-423-3596

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-423-3596

Diele Leading Mathed
Disk Loading Method:
Spring Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Safeguard class ars
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+225.0/+305.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
6.625 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.687 inches all ends
Second Connection Face To Centerline Distance:
6.000 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Steel comp 316 stem
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-01-423-3596

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0