NSN 4820-01-423-5693

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-423-5693

Diale Leading Mathed
Disk Loading Method: Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
300.0 degrees fahrenheit single response
End Application:
Osprey class mhc
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+75.0/+110.0 pounds per square inch
Maximum Operating Pressure:
750.0 pounds per square inch single response
Outside Diameter:
5.062 inches all ends
Thickness:
0.437 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
4.750 inches
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy body
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-423-5693

Safety Relief Valve - Page 2 of 2



Demi			

No

Fiig:

A046b0