NSN 4820-01-424-9866

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-424-9866
Bolt Hole Quantity:
8 2nd end
Maximum Operating Temp:
650.0 degrees fahrenheit single response
End Application:
Whidbey island class Isd
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+146.0/+164.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
7.500 inches 1st end
Thickness:
0.813 inches 2nd end
First Connection Face To Centerline Distance:
4.875 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
5.375 inches
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
5.000 inches 1st end
Special Features:
Marine service approved
Material:
Stainless steel stem
Material Specification:

Aisi 304 assn standard single material response flow control device

NSN 4820-01-424-9866

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0